

# STAR CABLE

Portable Multicables

The economical solution for professional 6-circuit applications.

	WDP1214T	WDP1219T
GENERAL	12 AWG 14 Conductor control cable to UL2586 using UL1015 singles. Flexible multicable for distribution of six "1K" or "2K" lighting circuits with bussed grounds.	12 AWG 19 Conductor control cable to UL2586 using UL1015 singles. Flexible multicable for lighting or audio.
CONDUCTORS	12 AWG bare copper 65 x 30, UL1015.	
INSULATION	Black PVC, 105 degree C rated. Minimum insulation thickness, 27 mils at any point. Conductors identified with white ink, sequentially numbered. The numbers correspond with ProSeries, KC and Socapex 19 pin contact numbering.	
ASSEMBLY	Planetary layup around a central PVC core. The conductors are Talc coated for flexibility and to ease stripping.	
JACKET	Black PVC, pressure extruded. 105 degree C rated, UL2586 requirements.	
MARKING	E177740 STYLE 2586 105C 600V 14 COND 12 AWG - cUL AWM I/IIA 105C 600V FT-1 STARCABLE	E177740 STYLE 2586 105C 600V 19 COND 12 AWG - cUL AWM I/IIA 105C 600V FT-1 STARCABLE
OUTSIDE DIAMETER	0.82" Nominal	0.99" Nominal
WEIGHT	520 lbs per 1000 ft.	720 lbs per 1000 ft.

THE DATA PRODUCED IN THIS DOCUMENT IS NOT BINDING AND CAN BE VARIED AS A CONSEQUENCE OF MODIFICATION AND / OR IMPROVEMENT DEEMED NECESSARY BY TMB



LITSTARCABLE-081507



## LOS ANGELES

10643 Glenoaks Blvd.  
Pacoima, CA 91331  
USA

Tel: +1 818.899.8818  
Fax: +1 818.899.8813

## LONDON

21 Armstrong Way  
Southall  
UB2 4SD England

Tel: +44 (0)20.8574.9700  
Fax: +44 (0)20.8574.9701

## NEW YORK

100 Asia Place  
Carlstadt, NJ 07072  
USA

Tel: +1 201.896.8600  
Fax: +1 201.896.8601

## BEIJING

No. 309, Building 6  
Sanlitun Nanlu  
Chaoyang District  
Beijing, China 100027

Tel: +86 10.8492.1587  
Fax: +86 10.8492.7635

## TORONTO

409 Saddler St. West  
Box 654, Durham  
Ontario NOG-1R0

Tel: +1 519.369.9990  
Fax: +1 519.369.9992