DATAPLEX® DEVICES

ETHERNET-DMX NODES

High-performance, signal management solutions that won't break the bank!

- Glitch-free processing of up to six ArtNet/sACN DMX 512/RDM universes
- Complete, extensive menu of useful configuration options
- User-friendly configuration via browser interface
- ProPlex Software-ready*, for simple yet powerful configuration and multi-unit system management
- Merge DMX/RDM, ArtNet and sACN data from multiple sources
- Full bi-directional functionality. Input or output on any DMX port
- Three DMX connection versions – Neutrik™ XLR, or Pluggable Terminal Block (PTB)
- High quality, professional-grade components and construction

*Download ProPlex Software for free at https://tmb.com/proplex-software

Worldwide Exclusive Distribution

Los Angeles +1 818.899.8818
London +44 (0)20.8574.9700
New York +1 201.896.8600
tmb www.tmb.com
Toronto +1 519.538.0888
Beijing +86 10.8492.1587
Riga +371 6389 8886

© 2026, TMB. All rights reserved. LITDPXNODE Effective: 6 August 2026
Specifications are subject to change without notice. This information supersedes all previously supplied information.

sales@tmb.com

Specifications		
Model	Dataplex Node 1x6 XLR	Dataplex Node 1x6 PTB
Part Number	DPNODE665XLR	DPNODE663PTB
Ethernet Ports	1	
DMX Ports	6	
RDM support	Yes	
In/Out/Out Isolation	Optical, up to 1000V	
Network Protocols	Art-Net, sACN (E1.31)	
Power	100-240 VAC, 50-60 Hz	
Power Consumption	10 W max.	
Power Connector	IEC with fuse holder, accepts IEC C13 cable (included)	
Fuse	5x20 mm 1A, 250V	
Ethernet Connector	Neutrik EtherCon RJ45	
DMX Connections	Neutrik XLR 5-Pin Female	Pluggable Terminal Block (PTB) 3-terminal (mating connectors included)
DMX Wire Size Range	N/A	28-13 AWG [0.08-2.5 mm²]
Cooling	Convection	
Operating Temp.	-4 to +104 °F [-20 to +40 °C]	
Unit Dimensions (WxHxD)	19 x 1.72 x 4.3 in [482.6 x 43.7 x 109.1 mm]	
Shipping Dimensions (WxHxD)	20.5 x 3.5 x 7.38 in [520.7 x 88.9 x 187.5 mm]	
Unit Weight	3.3 lb [1.5 kg]	3.3 lb [1.5 kg]
Shipping Weight	3.5 lb [1.59 kg]	3.5 lb [1.59 kg]

Dimensions in inches [mm]
XLR Models



© 2026, TMB. All rights reserved. LITDPXNODE Effective: 6 August 2026
Specifications are subject to change without notice. This information supersedes all previously supplied information.

Dimensions in inches [mm]
PTB Models



© 2026, TMB. All rights reserved. LITDPXNODE Effective: 6 August 2026
Specifications are subject to change without notice. This information supersedes all previously supplied information.

Ordering Codes	
Part Number	Item
DPNODE665XLR	Dataplex Node 1x6, XLR Connectors
DPNODE663PTB	Dataplex Node 1x6, PTB Connections

DMX Pinouts					
Connector	Pin 1	Pin 2	Pin 3	Pin 4	Pin 5
XLR	Shield	Data-	Data+	Unused	Unused
PTB	Shield	Data-	Data+	N/A	N/A

Riser Diagram



© 2026, TMB. All rights reserved. LITDPXNODE Effective: 6 August 2026
Specifications are subject to change without notice. This information supersedes all previously supplied information.