



# Festoon



## Low voltage “green” LED system with shatterproof outdoor-rated bulbs


- “Old School” classic look without the headaches
- Clear V6 and V12 “Filament” versions provide beautiful, warm, vintage look
- Frosted version in warm and cool white, plus a selection of rich, deep colors
- 24 Volts – Safe for public areas.
- 120V ETL Listed “Filament” lamps available! (V6 and V12)
- Lasts for years!



### The perfect choice for:

- |               |                   |
|---------------|-------------------|
| • Restaurants | • Bridges         |
| • Theme parks | • Casinos         |
| • Retail      | • Stage Sets      |
| • Malls       | • Film/TV Sets    |
| • Signage     | • Walkways        |
| • Parks       | • Boats           |
| • Festivals   | • Safety Lighting |
| • Events      | • And more!!      |
| • Buildings   |                   |

**Filament Lamps & Round Festoon Cable Now**



Designed in Australia

**Exclusive Distribution – The Americas, Europe, and Asia**

Innovative, Performance-Driven Show Technology Since 1983

tmb.com

Los Angeles  
+1 818-899-8818

London  
+44 (0)20-8574-9700

New York  
+1 201-896-8600

Beijing  
+86 10-8492-1587

Toronto  
+1 519-538-0888



## Available Lamp Options

			
WARM WHITE G45 "FILAMENT" V12 LED 120 Volt AC 1 Watt	WARM WHITE G45 "FILAMENT" V6 LED 120 Volt AC 0.5 Watt	WARM WHITE G45 "FILAMENT" V12 LED 24 Volt AC/DC 1 Watt	WARM WHITE G45 "FILAMENT" V6 LED 24 Volt AC/DC 0.5 Watt
			
RED G45 21 SMD LED 24 Volt AC/DC 1.5 Watt	BLUE G45 21 SMD LED 24 Volt AC/DC 1.5 Watt	GREEN G45 21 SMD LED 24 Volt AC/DC 1.5 Watt	PINK G45 21 SMD LED 24 Volt AC/DC 1.5 Watt
			
YELLOW G45 21 SMD LED 24 Volt AC/DC 1.5 Watt	ORANGE G45 21 SMD LED 24 Volt AC/DC 1.5 Watt	COOL WHITE PEARL G45 21 SMD LED 24 Volt AC/DC 1.5 Watt	WARM WHITE PEARL G45 21 SMD LED 24 Volt AC/DC 1.5 Watt

## Lamp Specifications

Part Number	Item	Lumen Output (LM)	Kelvin (K)	Voltage (V)	Watt (W)
FIRFESV12120VE	Warm white V12 "Filament", G45 round	39.8	2200	120 VAC	1
FIRFESV6120VE	Warm white V6 "Filament", G45 round	21.1	2200	120 VAC	0.5
FIRFESV12LAMPE	Warm white V12 "Filament", G45 round	39.8	2200	24 VAC/DC	1
FIRFESV6LAMPE	Warm white V6 "Filament", G45 round	21.1	2200	24 VAC/DC	0.5
FIRFESRDLAMP	Red, 21 SMD LED, G45 round	11.7	-	24 VAC/DC	1.5
FIRFESBLLAMP	Blue, 21 SMD LED, G45 round	11.6	-	24 VAC/DC	1.5
FIRFESGNLAMP	Green, 21 SMD LED, G45 round	53.3	-	24 VAC/DC	1.5
FIRFESPKLAMP	Pink, 21 SMD LED, G45 round	12.8	-	24 VAC/DC	1.5
FIRFESYWLAMP	Yellow, 21 SMD LED, G45 round	17.9	-	24 VAC/DC	1.5
FIRFESORLAMP	Orange, 21 SMD LED, G45 round	8.1	-	24 VAC/DC	1.5
FIRFESCWFLAMP	Cool White, 21 SMD LED, G45 round	70.2	5600	24 VAC/DC	1.5
FIRFESWWFLAMP	Warm White, 21 SMD LED, G45 round	68.4	2030	24 VAC/DC	1.5

Note: For outdoor use, application of a thin coat of silicone grease to lamp's metal screw base before inserting in socket is recommended.

## Firefly Festoon Cables

- IP44 Rated. Weatherproof flange protects lamp holders and lamp bases from moisture.
- Round and Flat cables available. Flat cable is self-leveling for ease of installation. Round cable is available in suspended and inline versions.
- Round cables are ETL Listed and retain listing even when cut to length in the field
- Cables are self-supporting up to 10 meters. Max. continuous cable run 40 meters.

### Round Festoon Cables

Available in black. Round cable with suspended or inline E26 sockets. Imperial socket spacing.

Type	Spacing				
Inline	12 in	15 in <sup>1</sup>	18 in	24 in	36 in
Suspended	12 in	-	-	24 in	-

<sup>1</sup>Available by special order, MOQ may apply



### Flat, Self-Leveling Festoon Cables<sup>2</sup>

Available in black or white. Flat design ensures uniform lamp orientation. Metric E27 socket spacing.

Color	Spacing					
Black	15 cm	20 cm	40 cm	50 cm	90 cm	1.5 meter
White	-	-	-	50 cm	90 cm	-

<sup>2</sup>Available by special order, MOQ may apply

