

2 conductors 20AWG stranded bare copper, polyethylene insulated, overall braid shielded, PVC jacketed microphone cable.



Specifications		
Conductor	AWG Size and Stranding	20 AWG [0.52 mm ²] 41 strands 36 AWG
	Material	Bare annealed copper
Insulation	Material	Polyethylene
	Wall Thickness	0.020" [0.51 mm] nominal
	Diameter	0.078" +/- 0.002" [1.98 mm +/- 0.05 mm]
	Color Code	Black/White
Assembly	Lay Length	2 1/2" [63.5 mm] maximum left hand
	Fillers	Paper as required
Shield	Material	Bare annealed copper braid
	Coverage	85% nominal
Jacket	Material	Matte finish polyvinyl chloride
	Colors	Black, Blue, Red
	Wall Thickness	0.040" [1.01 mm] nominal
	Diameter	0.260" +/- 0.005" [6.6 mm +/- 0.13 mm]
Markings	Type	Surface printing in white ink
	Legend	PROCABLE AUDIO PROFESSIONAL BRAIDED SHIELD BALANCED MICROPHONE CABLE, MADE IN USA
Electrical Specifications	Capacitance Between Conductors	21 pF/ft @ 1 kHz
	Capacitance Conductor to Shield	37 pF/ft @ 1 kHz
	Characteristic Impedance	70 Ohms @ 1 MHz
	Resistance at 20°C	10.3 Ohms/1000 ft.
Physical	Weight	50 lbs. per 1000' [74.4 Kg/Km]
	Stock Length	Black: 500', 1000' plastic spool in box. 2500' plywood spool. Colors: 1000' plywood spool

RoHS
Compliant

Worldwide Exclusive Distribution

sales@tmb.com

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

tmb
www.tmb.com

New York
+1 201.896.8600

Beijing
+86 10.8492.1587

Toronto
+1 519.538.0888