

The Leader in Touring Technology, Now Coming to a Building Near You!



**Optically isolated DMX Splitter
with 1 input, 4 outputs**

- 2ms DMX regeneration, automatically fixes “bad” DMX signals
- Versions available with or without RDM
- Pluggable Terminal Block (PTB) screw terminals for bare-wire, installation flexibility
- Complete range of DIN Rail Devices and Drives to make a complete system!



Indoor / Outdoor 12” and 24”
complete, pre-wired NEMA
enclosure kits available



Worldwide Exclusive Distribution

sales@tmb.com

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

tmb
www.tmb.com

New York
+1 201.896.8600

Beijing
+86 10.8492.1587

Toronto
+1 519.538.0888

ProPlex DIN Rail Opto-Splitter 4 Specifications		
Part Number	PPDSDIN14RA	PPDSDIN14MDA
RDM support	Yes	No
Operating Voltage	24 VDC (Requires external power supply)	
Power Consumption	10W	
Number of Inputs	1	
Number of Outputs	4 +1 Thru	
Number of Universes	1	
Power Input	Pluggable Terminal Block (PTB) 2-terminal ¹	
Data Input	Pluggable Terminal Block (PTB) 3-terminal ¹	
Data Thru	Pluggable Terminal Block (PTB) 3-terminal ¹	
Data Outputs	4x Pluggable Terminal Block (PTB) 3-terminal ¹	
Operating Temp.	-22 °F - 104 °F [-30 °C - +40 °C]	
Dimensions (HxWxD)	1.55" x 4.1" x 3.63" [39.5 x 104 x 92.3 mm]	
Weight	6.13 oz [174 g]	

¹ Included

