

Low Smoke Zero Halogen 0.22 mm² 1-Pair DMX Installation Cable



Specifications		
Part Number		PC242LSZH
Cores	Material	24 AWG [0.22 mm ²] stranded bare copper
	Stranding	28 x 0.1 mm
Insulation	Material	Polyethylene
	Colour Code	Red/Black
Assembly		2 cores [1 twisted pair]
Shield		Aluminium/Polyethylene foil metal inside, 100% coverage
Drain	Material	24 AWG [0.24 mm ²] stranded tinned copper
	Stranding	19 x 0.127 mm
Jacket	Material	EPDM, pressure extruded, UV Resistant
	Colour	Black
	Overall Diameter	3.2 mm +/- 0.15 mm
	Shorehardness (A)	80 +/- 3
	Legend	PROPLEX PC242LSZH 24AWG 0.22MM 1-PAIR SHIELDED CONTROL CABLE LSZH UV RESISTANT INSTALLATION CABLE
Physical	Weight	8.4 lb/mft [12.5 kg/km]
	Temperature Rating	-10 °C to +80 °C Static -30 °C to +80 °C Operating
Electrical	Insulation Resistance	20 MOhm/km at 20 °C max.
	Conductor Resistance	85 Ohm/km at 20 °C max.
	Operating Voltage	50 / 75V AC/DC max.
	Test Voltage	>1 kV

RoHS
Compliant

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

New York
+1 201.896.8600

tmb
www.tmb.com

Toronto
+1 519.538.0888

Beijing
+86 10.8492.1587

Riga
+371 6389 8886