ProPlex®

INSTALLATION DATA CABLE
PC226T

Designed for maximum ease of installation. Specifications Guaranteed.

CL2 UL-Listed low capacitance data cable, overall foil and braid shielding with drain wire. UV resistant. Fully rated for installations, yet easy handling for light-duty portable applications.

Specifications		
Part Number		PC226T
Conductors	Size and Stranding	22 AWG [0.34 mm²] stranded 19 x 34
	Material	Tinned, annealed copper
Insulation	Material	Foam HDPE, 60° C, 300 Volt
	Wall Thickness	0.016 in [0.41 mm] nom.
	Diameter	0.064 in [1.63 mm] nom.
	Color Code	Black/White, Red/Green, Blue/Orange
Shields	Inner Shield	Aluminum/mylar, 100% coverage with drain wire.
	Drain	22 AWG [0.34 mm²] Tinned, annealed copper stranded 19 x 34.
	Outer Shield	Tinned copper braid, 75% coverage.
Jacket	Material	UL listed PVC compound. The UL testing of the compound includes exposure to sunlight (UV, visible and IR), both rain and salt water, and temperature fluctuations, over 720 hours. After exposure the physical properties of the jacket are tested for, and must meet, a minimum retention of original properties. PC224TW is also fungus resistant.
	Wall Thickness	0.040 in [1 mm] nom.
	Tensile Strength	1,500 psi
	Jacket Color	Black
	Legend	PROPLEX PC226T 22 AWG 3-PAIR LOW-CAP SHIELDED CONTROL CABLE CL2 (UL) E177741 FT1 UV RESISTANT INSTALLATION CABLE
Physical	Assembly	Pairs cabled with Kevlar strength member and fillers.
	Outside Diameter	0.33 in [8.38 mm] nom.
	Weight	63 lbs. per 1,000 ft. [89.8 Kg/Km]. Ordered per reel at a length of 1000 ft.
	Temperature	Plus 60 °C, minus 20 °C
	Bend Radius	1.7 in [43.2 mm] min.
	Pull Tension	36 lbs. [16.3 Kg] max.
Electrical	Conductivity	15.5 Ohms (max.) @ 20 °C
	Characteristic Impedance	110 Ohms @ 1 MHz
	Capacitance	13 pf/ft. nom. conductor-to-conductor
		27 pf/ft. nom. conductor-to-shield
	Inductance	0.16 uH / ft. nom.
Listing		CL2 UL-Listed

Note: Purchase quantities are in 1000' reels

RoHS Compliant

Worldwide Exclusive Distribution

UL LISTED

Los Angeles +1 818.899.8818
London +44 (0)20.8574.9700
New York +1 201.896.8600
tmb www.tmb.com
Toronto +1 519.538.0888
Beijing +86 10.8492.1587
Riga +371 6389 8886

© 2022, TMB. All rights reserved. LITPC226T Effective: 7 December 2022
Specifications are subject to change without notice. This information supersedes all previously supplied information.

sales@tmb.com