



**Designed for maximum ease of installation.
Specifications Guaranteed.**

CL2 UL-Listed low capacitance data cable, overall foil and braid shielding with drain wire. UV resistant. Fully rated for installations, yet easy handling for light-duty portable applications.

Specifications

Part Number	PC226T	
Conductors	Size and Stranding	22 AWG [0.34 mm ²] stranded 19 x 34
	Material	Tinned, annealed copper
Insulation	Material	Foam HDPE, 60° C, 300 Volt
	Wall Thickness	0.016 in [0.41 mm] nom.
	Diameter	0.064 in [1.63 mm] nom.
	Color Code	Black/White, Red/Green, Blue/Orange
Shields	Inner Shield	Aluminum/mylar, 100% coverage with drain wire.
	Drain	22 AWG [0.34 mm ²] Tinned, annealed copper stranded 19 x 34.
	Outer Shield	Tinned copper braid, 75% coverage.
Jacket	Material	UL listed PVC compound. The UL testing of the compound includes exposure to sunlight (UV, visible and IR), both rain and salt water, and temperature fluctuations, over 720 hours. After exposure the physical properties of the jacket are tested for, and must meet, a minimum retention of original properties. PC224TW is also fungus resistant.
	Wall Thickness	0.040 in [1 mm] nom.
	Tensile Strength	1,500 psi
	Jacket Color	Black
	Legend	PROPLEX PC226T 22 AWG 3-PAIR LOW-CAP SHIELDED CONTROL CABLE CL2 (UL) E177741 FT1 UV RESISTANT INSTALLATION CABLE
Physical	Assembly	Pairs cabled with Kevlar strength member and fillers.
	Outside Diameter	0.33 in [8.38 mm] nom.
	Weight	63 lbs. per 1,000 ft. [89.8 Kg/Km]
	Temperature	Plus 60 °C, minus 20 °C
	Bend Radius	1.7 in [43.2 mm] min.
	Pull Tension	36 lbs. [16.3 Kg] max.
Electrical	Conductivity	15.5 Ohms (max.) @ 20 °C
	Characteristic Impedance	110 Ohms @ 1 MHz
	Capacitance	13 pf/ft. nom. conductor-to-conductor
		27 pf/ft. nom. conductor-to-shield
Inductance	0.16 uH / ft. nom.	
Listing	CL2 UL-Listed	

RoHS
Compliant



Worldwide Exclusive Distribution

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

New York
+1 201.896.8600

tmb
www.tmb.com
sales@tmb.com

Toronto
+1 519.538.0888

Beijing
+86 10.8492.1587

Riga
+371 6389 8886