


Makes Networking Easier and More Accessible!



Available with
8 or 16 ports
with PoE!



Rear RackMount Kit
option available

- EZ-User configurable, high-throughput Gigabit Switch
- Simultaneously separate and distribute up to four discrete networks – e.g lighting, audio, media, content, console, communications – with a few button presses
- Two EZ-LANs do the work of up to 8 unmanaged Gigabit switches
- 16 ports assignable in up to four, four-port groups
- Add a second fibre or copper connection for automatic redundancy and twice the speed
- 16 EtherCon LAN ports, 2 EtherCon Trunk ports, 2 OpticalCon Trunk ports (Quad standard. Duo optional)
- Compatible with a wide range of entertainment-specific protocols, including AES67, ArtNet, Dante, GreenGo, HippoNet, HogNet, Livewire, MA-Net 2/3, Q-LAN, RAVENNA, RDMNet, sACN, and more!

EZ-LAN makes today's complex show networking easier and accessible for everyone. These simple to operate yet powerful Gigabit Ethernet switches distribute up to four discrete networks – lighting, audio, content, server, console, or communications – quickly, effortlessly, and simultaneously.

Users untrained in the complexities of managed networking can easily isolate networks and access and change VLAN assignments with a single button press.

With 16 ports, assignable in up to four separate groups, EZ-LAN is a revolutionary addition to the ProPlex Data Distribution range of multiple format data management systems, all designed and built to withstand "Life on the Road."



BUILT FOR THE ROAD!
DATA DISTRIBUTION YOU CAN DEPEND ON

ProPlex®
DATA DISTRIBUTION

Worldwide Exclusive Distribution

sales@tmb.com

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

tmb
www.tmb.com

New York
+1 201.896.8600

Beijing
+86 10.8492.1587

Toronto
+1 519.538.0888

Technical Specifications			
Part Number	PPEZL218R	PPEZLPOE8218R	PPEZLPOE16218R
Base TX 10/100/1000 Ports	18		
Fiber Optic Link Ports	2		
Optical Connectors	OpticalCon QUAD (DUO option available)		
Ethernet Connectors	EtherCon RJ45		
AC Power	100-240V, 50/60Hz		
Number of Ports with PoE	0	8	16
PoE type	-	"PoE+" (25W) also compatible with "PoE" (15W) devices	
PoE standards	-	802.3af and 802.3at	
Max unit power consumption	30W	270W	510W
Colour LCD display	No	Yes, 1.8"	
Custom switch configurations	No	Yes, via LCD menu	
Port status LEDs	Single-colour	RGB multicolour	
Operating Temperature	-20°C - +40°C		
EIA Rack Units	19" 2U		
Unit Dimensions (WxHxD)	19 x 3.5 x 12 in (483 x 90 x 305 mm)		
Shipping Dimensions (WxHxD)	21 x 7.75 x 15.5 in (533 x 197 x 394 mm)		
Unit Weight	10.8 lb (4.9 kg)	TBA	TBA
Shipping Weight	16.5 lb (7.5 kg)	TBA	TBA

EZ-LAN Network Example

