

**Robust 4-way motor control built into a Pelican[™] Case for ultimate portability.
Worthy of the name ProPower.**



- ETL listed!
- 7-Pin, P14, or Twistlock output connectors
- 100% duty cycle rated hydraulic magnetic main circuit breaker
- Power inlet connector options including: L14-30, L21-20, L21-30, CS6375, and CS8375. 30A power inlet rated at 4hp, 20A power inlet rated at 3hp. Available with or without power thru connector.
- Remote GO button pendant option
- Mechanically interlocked phase reversing contactor
- Made in U.S.A.

Worldwide Exclusive Distribution

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

New York
+1 201.896.8600

tmb
www.tmb.com
sales@tmb.com

Toronto
+1 519.538.0888

Beijing
+86 10.8492.1587

Riga
+371 6389 8886

Technical Specifications			
Model	7-Pin	14-Pin	2x NEMA Twist-lock
Part Number	PPRPORMTR7P	PPRPORMTR14P	PPRPORMTRTL
Power Input	30 Amp 120/208 3 Phase		
Power Input Connector	Male NEMA L21-30 (Power Thru connector available by special order)		
Main Breaker	30 Amp 3-Pole 100% duty cycle rated hydraulic magnetic		
Phase Reverse	Rotary switch and mechanically interlocked phase reversing contactor		
Control Switches	Panel-mounted Up/Down rocker switches with indicator lights		
GO Control	Shrouded GO button on panel (remote go pendant also available)		
Motor Outputs	4	4	4
Motor Connectors	Female 7-Pin Socapex™ compatible	Female P14	Power: Female NEMA L16-20 Control: Male NEMA L14-20
Housing	Pelican™ 1450 Case		Pelican™ 1520 Case
Unit Dimensions (WxHxD)	16.4 x 13 x 6.8 in [417 x 330 x 173 mm]		19.8 x 15.8 x 7.4 in [503 x 401 x 188 mm]
Shipping Dimensions (WxHxD)	TBA	TBA	TBA
Unit Weight	13 lb (5.9 kg)	TBA	18 lb (8.2 kg)
Shipping Weight	TBA	TBA	TBA

Ordering Codes

PPRPORMTR7P	4-Way Controller, 7-Pin
PPRPORMTR14P	4-Way Controller, 14-Pin
PPRPORMTRTL	4-Way Controller, Twist-Lock
PPRREMOTEGO	Remote GO Pendant