

THE PERFECT AV STAND

- Chrome plated steel stand w/geared column
- Versatile top head accepts 1 1/8" spigot (included), also has a pop-up 5/8" 'baby' male spigot
- Three-section column diameter: 2.17 in. (55 mm), 1.77 in. (45 mm), 1.5 in. (38 mm)
- Two risers extend simultaneously at 1.75 in. (4.4 cm) per handle turn
- Safety cable ensures simultaneous retrieval of all sections
- Leg diameter: 1.18 in. (30 mm)
- Includes one leveling leg
- Optional casters available or will fit other brands of casters



Self-Locking device prevents accidental drop-off for added safety.



Leveling leg for use on uneven terrain.



Built-in footstep.



Brake tension adjustable via hex key.



Pop-up 5/8" "baby" Spigot.



1 1/8" spigot included for fixture mounting.



SPECIFICATIONS

Closed Length	71.25 in. (181 cm)
Max. Height	149.6 in. (380 cm)
Base Diameter	50.4 in (128 cm)
Max. Lift Capacity	66.1 lbs. (30 kg)
Self Weight	49.4 lbs. (22.4 kg)

ORDERING CODES

KCG483T	ProStand, Chrome
KCG483TBK	ProStand, Black
ETCKC100S	Locking Caster Set

Worldwide Exclusive Distribution

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

New York
+1 201.896.8600

tmb
www.tmb.com

Toronto
+1 519.538.0888

Beijing
+86 10.8492.1587

Riga
+371 6389 8886