



Little brother of the fabulous Solaris Flare, Winner Live Design Product of the Year and PLASA Sustainability Award

**Super Bright
LED RGBW
Wash/ Strobe/ Blinder**



MORE SAVINGS! Simultaneous color wash and strobe in ONE fixture – Saves labor, time, space, energy, and cost.

MORE SMOOTH! Instantaneous RGBW color mixing with 1200Hz refresh rate – Smooth on-camera dimming.

MORE VERSATILE! Pixel-map feature divides into 1, 2, or 4 sections for ultimate control.

MORE SATURATED COLORS! Intense, deep reds and blues. Ultra-bright greens. Brilliant camera-friendly whites.

MORE FLEXIBLE! 36-degree beam angle optimized for most applications.



Worldwide Exclusive Distribution

sales@tmb.com

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700



New York
+1 201.896.8600

Beijing
+86 10.8492.1587

Toronto
+1 519.538.0888

Specifications	
Light sources	32 10W CREE® LEDs (divided in to 4 pixels)
Beam spread	36°
Colors	4- R, G, B, W
Average color wavelength (manufacturer rated)	Red: 625 nm
	Green: 530 nm
	Blue: 460 nm
	White: >5700K
Refresh rate	1200 Hz
Intensity control	16-bit or 8-bit
Control	DMX-512
Wireless control	Wireless option available by special order
AC power	90-277 VAC universal input, 50/60 Hz
Cooling	Air-cooled fan
Operating temperature	-20°C - +40°C
DMX channels	3-24 depending on control mode
DMX connectors	In/Out - XLR 5-pin F/M
Max. power draw	~400 W
Power connectors	In- PowerCon 20A blue + THRU- PowerCon grey
Fixing	Adjustable yoke
Fixture body	Powdercoated steel
Unit dimensions (HxWxD)	6.1 x 13.4 x 5.3 in [15.5 x 34 x 13.5 cm]
Shipping dimensions (HxWxD)	14 x 14 x 10 in [35.6 x 35.6 x 25.4 cm]
Unit weight	10.6 lb [4.8 kg]
Shipping weight	13 lb [5.9 kg]

Ordering Codes	
Ordering Code	Item
SOLFJ36R	Flare Jr fixture
SOLFJ36RW	Flare Jr fixture, wireless
SOLFJ36RWADD	Flare Jr wireless adder
SOLFJRKAS	Flare Jr Kasmer diffusion/filter holder
SOLFJRBKAS	Flare Jr Kasmer barndoor

Specifications and features are subject to change without notice.

