

## 15,000 WATT VERY BRIGHT INDOOR STROBES



Versatile strobes that can be used anywhere either flash or constant light is required. Ideal for theatre, concert, dance club, and rental company applications.

No comparable strobe in the world!

### FEATURES

- 450,000 lumens maximum output!
- DMX512 control
- Continuous lighting capability (120Hz)
- Automatically controlled electronic safety feature
- Auto voltage sensing
- Thermal shut-down feature
- Highly accurate flashing system
- Three phase system capability
- Compact size
- SELF-Test functions, LED indicators
- Optional controllers can execute pre-programmed or customized lightning sequences at the push of a button or triggered via DMX512



**Worldwide Exclusive Distribution**

[sales@tmb.com](mailto:sales@tmb.com)

Los Angeles  
+1 818.899.8818

London  
+44 (0)20.8574.9700

**tmb**  
[www.tmb.com](http://www.tmb.com)

New York  
+1 201.896.8600

Beijing  
+86 10.8492.1587

Toronto  
+1 519.538.0888

Specifications			
Lamp	Maximum continuous flash discharge	2.5 seconds	
	Frequency of continuous mode	120 Hz	
	Flash tube type	Proprietary Long Arc Xenon tube	
	Color temperature	5600° Kelvin	
Control Parameters	Intensity control		
	Adjustable flash frequency		
Electronic & Safety Devices	Overheating protection	80°C, 110 °C, self resetting	
	Self-test	Preprogrammed	
	Indicator LEDs	Red: Power Yellow: Mode/Protection Green: Data	
Control System	Digital display and pushbutton programming of parameters		
	Number of channels	2	
	Connection type	5-Pin XLR	
	Supported Protocols	DMX512	
Power Supply	Nominal mains voltage	190-260 VAC, 50-60 Hz	
	Power requirement	20A breaker	
	Max. power draw	Continuous	60A
		Turbo	32A
Fixture & Housing	Protection from breaking flash tube	Soft spring suspension system	
	Fixing	Adjustable yoke	
	Corrosion protection	Aluminum body	
	Unit Dimensions (HxWxD)	7.5" x 21.5" x 5.5" / 19 x 54.6 x 14 cm	
	Shipping Dimensions (HxWxD)	10.5" x 23.75" x 9" / 27 x 60.5 x 23 cm	
	Unit weight	7.8 lb. (3.6 Kg)	
	Shipping weight	10.6 lb. (4.8 Kg)	

## Dimensions

