



Description

Developed from over 30 years of engineering the world's most durable DMX cables, Starcable® DMX is a flexible economy cable, that handles and coils well, again and again. Top industry brand connectors and cable, Starcable represents an unparalleled combination of quality and affordability.

Features

- Heavy duty tour-grade PVC jacket offers dependability and long life
- Rugged industry standard black/gold connectors provide most reliable long-lasting connections
- Water and UV resistant, suitable for temporary outdoor use
- Extra flexible for ease-of-use
- Individually tested for performance and quality



The First and Still the Best!

TMB Pro Cables – High-quality custom cable assemblies for the entertainment production and staging industry since 1983. Over 60 highly skilled assembly technicians worldwide. Well over 400 years combined experience! Rigorous testing and quality control. Famous TMB Rush Service Normal!

SPECIFICATIONS		
Conductor	AWG Size and Stranding	26 AWG [0.15 mm ²] 19 strands 38 AWG
	Material	Bare annealed copper
Insulation	Material	Polyethylene
	Diameter	0.07" [1.8 mm]
	Color Code	Red/White
Assembly	Lay Length	60 mm left hand +/- 5 mm
	Fillers	Cotton Strand Y
Foil Shield	Material	AL-PT Foil, conductive side out towards braided shield
	Coverage	100%
Braid Shield	Material	16 x 4 Ø 0.10 mm bare annealed copper
	Coverage	> 60%
Jacket	Material	PVC
	Color	Black
	Diameter	0.230" +/- 0.006" [5.8 mm +/- 0.15 mm]
Markings	Type	Surface printing in white ink
	Legend	TMB Starcable DMX - WSCDMX5NB - 26AWG 1-pair low cap shielded control cable
Electrical	Characteristic Impedance	120 ohms @ 1 MHz
	Capacitance	75 pF/ft @ 1 kHz between conductors
		140 pF/ft @ 1 kHz conductor to shield
	Attenuation	2.0 dB / 100 m @ 1 MHz
	Conductor Resistance	117 G ohms/m @ 20°C nom.
Test Voltage	1,000 VAC @ 50 H, 1 min. Conductor to shield	
Physical	Working Temperature	-10 °C to +70 °C

Ordering Codes			
Part Number	Length	Unit Weight	Shipping Weight
WSCDMX5NB-5	5 ft.	0.30 lb [136 g]	0.50 lb [227 g]
WSCDMX5NB-10	10 ft.	0.45 lb [204 g]	0.65 lb [295 g]
WSCDMX5NB-25	25 ft.	0.80 lb [363 g]	1.00 lb [454 g]
WSCDMX5NB-50	50 ft.	1.40 lb [635 g]	1.60 lb [726 g]
WSCDMX5NB-100	100 ft.	2.50 lb [1134 g]	2.80 lb [1270 g]

RoHS
Compliant

 **LIMITED LIFETIME WARRANTY**
BUILD WITH CONFIDENCE

**Quality cables and tour-grade reliability from TMB,
the entertainment industry cable leader since 1983!**