

# ProPlex<sup>®</sup>

## CABLES FOR



## SYSTEMS

	<i>ProPlex</i> Cable	Application
DMX	<i>ProPlex</i> PC244T	<b>Installation DMX Cable</b> - For installation in conduit: easy stripping, color-coded foil on pairs. 2 pair, 24 AWG (0.25mm <sup>2</sup> ) data cable with individually shielded pairs. CM CMH.
	<i>ProPlex</i> PC244TP	<b>Plenum installation DMX cable</b> - Plenum. 2 pair, 24 AWG (0.25mm <sup>2</sup> ) data cable with individually shielded pairs. CMP.
	<i>ProPlex</i> PC224T	<b>Installation /portable (indoor/outdoor) / heavy-duty DMX cable</b> - 2 pair, 22 AWG (0.34mm <sup>2</sup> ) data cable with overall foil and braid shielding. CL2 FT1, UV and fungus resistant.
	<i>ProPlex</i> PC224P	<b>Extra heavy-duty portable (indoor/outdoor) DMX cable</b> - the first ever purpose-built DMX cable. Super durable with optimum handling characteristics, ideal for portable use. 2 pair, 22 AWG (0.34mm <sup>2</sup> ) data cable with overall foil and braid shielding.
CAT5e	<i>ProPlex</i> PCCAT5EPU	<b>Extra heavy-duty portable (indoor/outdoor) CAT5E cable</b> - 4 pair, 24 AWG (0.25mm <sup>2</sup> ), 100 Ohm S/FTP round cable, double shielded with Kevlar reinforcement, jacketed in black UV-resistant Polyurethane. Conforms to ISO / IEC 11801 CAT5E requirements. Meets all CAT5E horizontal specs up to 90 meters; all CAT5E horizontal specs except attenuation up to 100 meters.
	<i>ProPlex</i> PCCAT5EP26AWG	<b>Extra heavy-duty portable (indoor/outdoor) CAT5E patch cable</b> - 4 pair, 26 AWG (0.14mm <sup>2</sup> ), 100 Ohm SF/UTP round cable, overall double shielded with Kevlar reinforcement, jacketed in black UV-resistant Polyurethane. Conforms to ISO / IEC 11801 CAT5E requirements. Meets all CAT5E patch cable specs up to 10 meters.
RFU	<i>ProPlex</i> PC226T	<b>Installation / portable (indoor/outdoor) heavy-duty RFU cable</b> - 3 pair, 22 AWG (0.34mm <sup>2</sup> ) data cable with overall shielded pairs. CL2 FT1, UV and fungus resistant.
ETCLink	<i>ProPlex</i> PC226T	<b>Installation / portable (indoor/outdoor) heavy-duty RFU cable</b> - 3 pair, 22 AWG (0.34mm <sup>2</sup> ) data cable with overall shielded pairs. CL2 FT1, UV and fungus resistant.
ETC UnisonLink Power	<i>ProPlex</i> PCLP1PT	<b>Architectural node/button station cable.</b> Black low-voltage cable for installation in non-metallic conduit - 1 pair, 16 AWG (1.5 mm <sup>2</sup> ), with convenient 22 AWG (0.34mm <sup>2</sup> ) ground wire. CL3 FT1.
	<i>ProPlex</i> PCLP1PTP	<b>Plenum architectural node/button station cable.</b> White low-voltage cable for plenum installation - 1 pair, 16 AWG (1.5 mm <sup>2</sup> ), with 22 AWG (0.34mm <sup>2</sup> ) ground wire. CL3P FT1.
ETC UnisonLink & Display Power	<i>ProPlex</i> PCLP2PT	<b>Architectural node/button station and LCD display cable.</b> Black low-voltage cable for installation in non-metallic conduit - 2 pair, 16 AWG (1.5 mm <sup>2</sup> ), with convenient 14 AWG (2.5mm <sup>2</sup> ) ground wire. CL3 FT1.
	<i>ProPlex</i> PCLP2PTP	<b>Plenum architectural node/button station and LCD display cable.</b> White low-voltage cable for plenum installation - 2 pair, 16 AWG (1.5 mm <sup>2</sup> ), with 14 AWG (2.5mm <sup>2</sup> ) ground wire. CL3P FT1.

Innovative, Performance-Driven Show Technology Since 1983

tmb.com

Los Angeles

London

New York

Beijing

Toronto

+1 818-899-8818

+44 (0)20-8574-9700

+1 201-896-8600

+86 10-8492-1587

+1 519-538-0888

